QUARRY




Description

Quarry tile offers the combination of long wear and high slip resistance perfect for the highest demanding of environments. Craft breweries, commercial kitchens, schools, industrial applications, supermarkets, or anywhere slip resistance and durability are a must is where this product is fundamental.

Colors









Sizes











Technical Data

Specification Reference	Test Method	Test Result		
DCOF	ANSI A326.3	Oils & Greases (>0.55 Wet)		
Water Absorption	ASTM C373	> 3%		
Breaking Strength	ASTM C648	> 800 lbf		





Finish & Thickness

Abrasive, Ironspot Smooth, Matte, Textured | 12.7mm Finish varies per size and color -Refer to Color • Size • Finish Matrix

Lead Time

2-3 Weeks





Shade Variation

Location USA

Body Type

Ceramic

Color • Size • Finish Matrix

Color — Size & Thickness								
	Dark Grey	Dark Grey	Brown	Pewter	Pewter	Red	Red	Black
4" x8" x12.7mm	,							Matte
6"x6"x12.7mm	Abrasive	Ironspot Smooth	Matte	Matte	Textured	Abrasive	Ironspot Smooth	Matte
8" x8" x12.7mm	Abrasive					Abrasive		Matte
ound Top Covebase 6"x6"x12.7mm		Ironspot Smooth	Matte	Matte			Ironspot Smooth	Matte
ound Top Covebase Corner - Right or Left 6"x6"x12.7mm		Ironspot Smooth	Matte	Matte			Ironspot Smooth	Matte
ound Top Covebase In Corner 6"x6"x12.7mm		Ironspot Smooth	Matte	Matte			Ironspot Smooth	Matte
ound Top Covebase 6"x8"x12.7mm		Ironspot Smooth					Ironspot Smooth	Matte
ound Top Covebase Corner - Right or Left 6"x8"x12.7mm		Ironspot Smooth					Ironspot Smooth	Matte

Chart indicates available size, color, finish and thickness options. Shaded block indicates not available. Sizing is nominal for field tile, trims, and decors.





